

BO Motor Oil BV Rootven 10 5531 MB BLADEL The Netherlands E-mail: info@bomotoroil.com Tel.: (+31)497 - 38 48 47 Fax: (+31)497 - 38 40 55 KVK nr. 61804312 BTW nr. NL 854495538 B01 Rabobank 10.75.97.055 IBAN nr. NL57 RABO 0107 5970 55 BIC-code: RAB0<u>NL2U</u>

## TECHNICAL DATASHEET

Synthetic motor oil for 4-stroke motorcycles

**CONTROL SPORT HONDA** is a synthetic engine oil without a friction modifier and has been especially developed for 4-stroke motorcycles. This oil can also be applied in motorcycle transmissions where an API SF or SG is prescribed.

**CORS4 SPORT HONDA** is suitable for off road and cross applications and offers excellent protection against wear, deposits, sludge and oxidation under all conditions.

**CORPORT HONDA** has a low volatility, reducing oil thickening and oil consumption to a minimum.

Due to the sophisticated formulation, this oil offers an excellent protection to gearboxes and wet disc clutches and prevents from slippery and sticking clutches.

Despite the high loads between the toothed faces, the special oil thickener hardly breaks down, so that even at high temperatures, the viscosity stays in grade to assure a strong lubricant film.

At low temperatures **PRS4 SPORT HONDA** rapidly builds up a solid lubricant film for an optimum protection at the cold start.

## SPECFICATION

API SL/SH/SJ JASO MA CCMC G5 PD2

## VALUE ANALYSIS

		HONDA	ASTM	
Density 20C	Kg/L	0.875	D1298	650152
Viscosity 100C	cSt	13.9	D445	
Viscosity 40C	cSt	93	D445	6-10.0.0
Viscosity -25C	cP	<7000	D5293	
Viscosity Index		153	D2270	
Flash point COC	С	220	D92	
Pour point	С	-36	D6892	

## AVAILABLE **PACKAGING**

5111 - 1L, 5411 - 5L, 5521 - 20L, 5621 - 60L

The contents of this document is intended to enable the reader to orient themselves on properties and potential applications of BO Motor Oil products. The information in this document at any time and without notice be altered because of continuous product seearch and development. The analytical data are listed in this product data sheet are typical values. Minor deviations, which may occur during the morant manufacturing the text. The reader is advised to make the final product in consultation with the supplier.

www.bomotoroil.com