



PRODUCT INFORMATION


RACING 4 LUBE 10W60


Fully synthetic motor oil for 4-stroke motorcycles

 **Racing 4 Lube Fully Synthetic** is a full synthetic engine oil and contains a dedicated ester technology to provide extra protection against wear, deposits, sludge and oxidation under all conditions.


This oil can also be used in motorcycle transmissions where an API SF, SG, SH, SJ, SL or SM oil is prescribed.

 **Racing 4 Lube Fully Synthetic** is suitable for go karts, touring, racing, as well as for cross applications, under all conditions.

 **Racing 4 Lube Fully Synthetic** offers an excellent protection against wear, deposits, sludge and oxidation. Even under the most severe operating conditions air-absorption and foam building are minimised.

 **Racing 4 Lube Fully Synthetic** has a very low volatility by which oil thickening and oil consumption are reduced to a minimum. Due to the special formulation, this oil offers excellent protection to gearboxes and wet disc clutches.

Even under the extreme conditions in gearboxes, the selected oil thickener will hardly break down so that at high temperatures the viscosity stays in grade to guarantee a solid lubricant film.

At low temperatures  **Racing 4 Lube Fully Synthetic** 5W40 and 5W50 rapidly provides a solid lubricant film for an optimum protection of the engine at cold starts.

SPECIFICATION

API SL
API SM
JASO MA2
JASO MA

VALUE ANALYSIS

| | | 10W60 | ASTM |
|---------------------|----------|-------|-------|
| Density 20C | Kg/L | 0,857 | D1298 |
| Viscosity 100C | cSt | 24,6 | D445 |
| Viscosity 40C | cSt | 171 | D445 |
| Viscosity -30C | cP | <7000 | D5293 |
| Viscosity Index | | 175 | D2270 |
| Flash point COC | C | 225 | D92 |
| Pour Point | C | -33 | D97 |
| B.N. (HCLO4-method) | mg/KOH/g | 6,6 | D2896 |

AVAILABLE PACKAGING

52191 - 1L, 52151 - 4L, 52111 - 20L, 32111 - 30L, 52071 - 60L 52031 - 210L

The contents of this document is intended to enable the reader to orient themselves on properties and potential applications of BO Motor Oil products. The information in this document at any time and without notice be altered because of continuous product research and development. The analytical data are listed in this product data sheet are typical values. Minor deviations, which may occur during the normal manufacturing process of the product, the quality of the product does not affect. Although this text has been compiled with great care, the compiler accepts no liability for damage caused by incompleteness and / or inaccuracies in the text. The reader is advised to make the final product in consultation with the supplier.

We believe it's the right choice